

Which Audioscan is right for you?

Standard Fitting Tools	Verifit®2	Verifit®	Axiom®	RM500SL™
On-ear and test box (S-REM)	B			
Calibrated real speech stimuli				
Percentile analysis				
DSL®5, NAL-NL2, CAMFIT targets				
Multicurve	B			
ANSI 2009				
Frequency-lowering test stimuli				
User-supplied sound files				
FM fitting protocol				
Advanced Fitting Tools				
Audiometric data entry to 12.5kHz				
Wideband verification				
Noise reduction test	B			
Feedback test	B			
CROS/BiCROS fitting in Speechmap™				
Speechmap for telecoil	TT	TL		
Monitor headphones	B			
Directional test	B			
Occlusion effect test				
Battery drain measurements				*
Standard Ease of Use Features				
Context sensitive help				
Smart microphone calibration				
Smart sound field equalization				
Smart RECD transducer calibration				
NOAH module				
Advanced Ease of Use Features				
Heads-up help with instructive pictures				
L/R display swap				
Binaural Sound Field Assist				
Virtual keyboard				
Print to PDF (EMR compatible)				
PC control/display capability (On-top mode)				
Wireless networking				
Counseling Tools				
Sensory Loss Simulator™				
Audibar SII display				

B: Binaural features
 TT: Tele-test handset and T-loop
 TL: T-loop only
 *optional on RM500SL



20 Ludwig St., Dorchester ON, Canada, N0L 1G4

audioscan.com | USA 800-265-2093 | 519-268-3313 | info@audioscan.com